



A Textron Company

MODEL: MPT 800
TYPE: ELECTRIC POWERED TRUCK
MODEL YEAR: 2009
Part No.: 76195



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Battery Charger:** PowerWise™ 36QE high frequency, fully line compensating. 10 ft (3 m) DC Cord. Underwriters Lab. (U.L.) Listed, (C.S.A. Certified)
- Input: 110 – 120 Volt, 50/60 Hz, 8 amp
 - Output: 36 Volt at 16 amps. DC
- Motor:** 36 Volt DC series wound, brazed armature, solid copper windings
- Drive Train:** Direct motor shaft connected to transaxle pinion shaft
- Electrical System:** 36 Volt DC, six, 6 volt deep cycle batteries (115 minute minimum, 225 amp-hour @ 20 hr. discharge rate)
- Transaxle:** Differential with helical gears
- Brakes:** Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system
- Cargo Bed:** Roto-molded cross-linked polyethylene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

PRODUCT OVERVIEW

Dimensions

Overall Length	103.0 in (262 cm)
Overall Width	46.5 in (119 cm)
Overall Height (No Canopy)	48.6 in (123 cm) (Top of steering wheel)
Overall Height (With Canopy)	68.0 in (173 cm)
Wheel Base	65.5 in (166 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	4.3 in (11 cm)
Cargo Box Width (inside)	44.5 in (113 cm)
Cargo Box Length (inside)	30.5 in (77 cm)
Cargo Box Depth (inside)	7.5 in (19 cm)
Cargo Box Capacity	5.9 cu ft (0.17 m ³)
Cargo Box material	Roto-molded polyethylene

Vehicle Power

Power Source	36 Volts DC
Motor Type	Series Wound
Horsepower (kW)	2.5 hp (1.9 kW) @ 2700 rpm
Electrical System	36 Volt
Batteries (Qty, Type)	Six, 6 Volt Deep Cycle
Key or Pedal Start	Pedal Start
Battery Charger	36 V PowerWise QE, 120 VAC, UL & CSA
Speed Controller	Solid State 300 Amp Rated
Drive Train	Motor Shaft Direct Drive
Transaxle	Differential with helical gears

Gear Selection Forward-Neutral-Reverse

Rear Axle Ratio 12.44:1

Performance

Seating Capacity	2 Person
Dry Weight	675 lb (310 kg) (Without Batteries)
Curb Weight	1040 lb (470 kg)
Bed Load Capacity	500 lb (230 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	18.9 ft (5.76 m)
Intersecting Aisle Clearanc	N/A
Speed (Level Ground)	13 mph ± 0.5 mph (21 kph ± 0.8 kph)
Towing Capacity	500 lb (230 kg) max load

Steering & Suspension

Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tires	Turf Saver 18 x 8.50 - 8 (Load Range B)

Body & Chassis

Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection molded Geloy XTW
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Forest Green



A Textron Company

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld
TIRES & WHEELS:			
Front:			
Links 18 x 8.50 - 8 (4 Ply Rated)	●		
USA Trail 18 x 8.50 - 8 (Load Range C)		●	
Turf Saver 18 x 8.50 - 8 (Load Range B)		●	
Rear:			
Turf Saver 18 x 8.50 - 8 (Load Range B)	●		
USA Trail 18 x 8.50 - 8 (Load Range C)		●	
Links 18 x 8.50 - 8 (4 Ply Rated)		●	
Wheel Covers:			
Spoke, Black & Gold		●	
Spoke, Black & Silver		●	
COLORS:			
Body Color (Forest Green)	●		
Body Color (Ivory)		●	
Body Color (Bright White)		●	
Body Color (Yellow)		●	
Body Color (Orange)		●	
Body Color (Flame Red)		●	
Seating:			
Seat Color (Tan)	●		
Seat Color (Oyster)		●	
Seat Color (White)		●	
Custom Seat Color		●	
OTHER PERFORMANCE:			
Ash Tray		●	●
Differential Guard		●	
Front Bumper & Guard (Black)		●	
Front Hydraulic Disc Brakes		●	
Glove Box Door (Locking) Driver Side		●	
Glove Box Door (Locking) Passenger Side		●	
Rear View Mirror (Sun Canopy Required)			
ELECTRICAL:			
Battery Chargers:			
36 V PowerWise QE, 120 VAC, UL/CSA 18 Ft DC Cord		●	
36 Volt PowerWise On-Board, 120 VAC, UL & CSA		●	
Charger Receptacle Cover (Use with On-Board Charger)		●	
36 Volt Lester, 230 VAC, 50 Hz		●	
Lighting Package:			
Headlights	●		
Headlights & Taillights	●		
Strobe Light		●	
Turn Signals with 4-Way Flashers		●	
Work Lights		●	
Work Lights with Strobe Light		●	

Item	Std	Opt	Fld
Miscellaneous:			
DC Converter		●	
Horn	●		
Hour Meter		●	
State of Charge Meter	●		
Unique Individual Key Switch		●	
HAULING & TOWING:			
1 7/8 in (48 mm) Ball (Rcvr Reqd)		●	
1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		●	
2 in (5 cm) Receiver (Rear)		●	
Angle (Rcvr Reqd)		●	
Angle, Drop (Rcvr Reqd)		●	
Clevis (Rcvr Reqd)		●	
Clevis, Drop (Rcvr Reqd)		●	
Miscellaneous:			
Gas Spring Assisted Load Bed		●	
Power Dump (Electric)		●	
Trailer, Dump (Poly Bed)			●
Trailer, Dump (Steel Bed)			●
WEATHER PROTECTION:			
Brush Guard Cage for Windshield & Top			●
Sun Canopy (Top) Champagne			●
Sun Canopy (Top) Tan			●
Sun Canopy (Top) Tan (Brush Guard Cage Required)			●
Weather Enclosure, Tan (3 Side, Top & Windshield Req'd)			●
Weather Enclosure, White (3 Side, Top & Windshield Req'd)			●
Windshield (Brush Guard Cage Required)			●
Windshield Flat			●
Windshield Flat Lexan®			●
Windshield Fold Down			●
Windshield Fold Down Lexan®			●
VEHICLE CAB:			
Steel Cab (Tan):			●
Steel Cab (White):			●
Steel Cab (Non Standard Color):			●
Beacon, Amber (Cab Required)			●
Defroster/Fan (Cab Required)			●
Dome Light (Cab Required)			●
Doors (Steel) Tan (Cab Required)			●
Doors (Steel) White (Cab Required)			●
Doors (Steel) Non Standard Color (Cab Required)			●
Doors (Vinyl) Tan (Cab Required)			●
Rear View Mirror (Cab Required)			●
Strobe Light (Cab Required)			●
Switch Panel (Cab Required)			●
Windshield Wiper (Cab Required)			●